



Submitted Model No.:

Specific Features:



lacktriangle Designate proper finish suffix

Available LHP Handle Options





SPECIALTY FAUCETS

- Three Handle Bidet Valve
- Four Hole Installation

STANDARD SPECIFICATIONS:

- Solid fabricated brass end valves
- Widespread flexible mounting installation
- Clear knob handles with red/blue indicators or LHP-Less Handle Program. See handle options below.
- Directional handle for rim flush or rosette spray.
- Control mechanism is a rotating cylinder type with stainless steel plate and 180° rotation, with replaceable non-metallic seats operating in stainless steel lined sockets.
- Hot and cold stems are interchangeable.
- Temperature and volume controlled with handles.
- All operating parts shall be replaceable from the top.
- 3/8" O.D. copper tube inlets with 1/2"-14 NPSM adapters.
- Metal pop-up drain assembly.
- Model 44 series has vacuum breaker.
- For handle H253 you must also order RP62961, which contains 62480 base and 1713 bonnet.

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

ASME A112.18.1 / CSA B125.1 Indicates compliance to ICC/ANSI A117.1

Available LHP Handle Accent Options with Matching Lift Knobs



A24▲



